

HOFMANN®



Geodyna 2300

WHEEL BALANCER

Geodyna 2300

The Hofmann 2300 entry-level wheel balancer is designed for single-bay shops and quick-lube facilities. The 2300 is equipped with balancing features found on more expensive machine, yet is affordably priced.

- **Unsurpassed accuracy**
Improved balancing technology has 512 precise weight positions, twice as many as other brands. Special "user-calibration" calibrates balancer in two easy steps, guaranteeing accuracy.
- **Longer mounting shaft**
40mm balancer shaft is 30% larger than most competitive brands. This standard feature allows mounting of wider wheels. Ziplock™ quick nut provides fastest wheel mounting/demounting system in the industry.
- **Ten balancing modes**
The 2300 is equipped with ten different balancing modes, five alloy modes, two hidden weight, "Pro-Match" tire /wheel matching, dynamic and static to handle most wheel applications.
- **"HSP" Weight Placement**
Patented Hidden Spoke Placement allows the operator to hide correction weights behind the spokes on expensive rims that have no outer flange
- **Automatic data entry**
This time saving feature precisely enters the rim distance automatically, eliminating operator errors and customer comebacks.

WHEEL BALANCER

Specifications

Shipping weight300lbs
Rim width range1.0" – 20.0"
Rim diameter range8.0" - 30.0"
Max. tire diameter48"
Max. wheel weight150lbs
Electric requirement115V 50/60hz 1ph
Motor1.0 Hp
Cycle timeFrom 6 seconds
Read-outsGram or Ounce
Accuracy1g or 0.05 oz
Balancing Modes10

Standard Accessories

Automotive Cone Kit1 5/8"-4 1/2"
"Ziplock" quick nut, pressure cup with rubber scratch proof cap, rim width gauge, calibration tool, storage pegs.

Optional Accessories:

Lt. Truck Cone Kit for 1/2, 3/4, and 1 Ton (4.25" - 6.85")8100068
Truck Cone Kit for 3/4 and 1 Ton (7.7" - 8.75")2401776
Universal Rear-mount Lugnut Adt. For 3,4,5,6 and 8 stud wheels8100007
Universal Front-mount Lugnut Adt. For 3,4,5,6 and 8 stud wheels8100006
70mm Standard studs, use with 8100006 (set 5)2402263
73mm Spring-loaded studs, use with 8100006 (set 5)2402266
80mm Truck studs, use with 8100006 (set5)2402262
80mm Porsche studs, use with 8100006 (set 5)2402265
Steel "Ziplock" Wing Nut6411408
8" Alloy Pressure Cup6415368

Hofmann manufactures a complete line of wheel service equipment.



Imaging & Conventional Alignment Equipment



Tire changer designed to service all automotive tires.



Combination brake lathes for rotors, drums and flywheels.

HOFMANN®
USA

309 Exchange Avenue • Conway, AR 72032
(800) 251-4500 • (501) 450-1581
Fax (501) 450-2085 • www.hofmann-usa.com

HOFMANN®
Canada

6500 Millcreek Drive • Mississauga, ONT L5N 4G4
(800) 267-2185 • (866) 812-5316
Fax (905) 821-2073 • www.hofmann.ca
E-mail: info@hofmann.ca