

# 2600/2800

## WHEEL BALANCER

**Premium wheel balancers designed for speed, accuracy and dependability.**

- **Unsurpassed accuracy**  
Improved balancing technology has 512 precise weight positions. Special "user-calibration" calibrates and readjusts the balancer in two easy steps, guaranteeing accuracy.
- **Longer mounting shaft**  
40mm balancer shaft is 30% larger than most competitive brands. Allows mounting of wider wheels using standard accessories. "Ziplock" quick nut provides fastest wheel mounting/demounting system in the industry.
- **Ten balancing modes**  
The 2600/2800 is equipped with ten different balancing modes, five alloy modes, two hidden weight, "Pro-Match" tire/wheel matching, dynamic and static to handle most wheel applications.
- **"HSP"/"OSP" Weight Placement**  
Patented Hidden Spoke Placement allows the operator to hide correction weights behind the spokes on expensive rims that have no outer flange. Patented Operator Selectable Positioning allows the operator to select the correction location by rim design.
- **Automatic data entry/weight location**  
This time saving feature on the 2600 precisely enters the rim diameter and distance automatically; the 2800 is equipped with all automatic wheel weight indexing. This time saving feature rotates the tire automatically to the correction location.

Hofmann offers a complete line of wheel service equipment.

### Specifications

Shipping weight.....	400lbs
Rim width range.....	1.0" – 20.0"
Rim diameter range.....	8.0" - 24.0"
Max. tire diameter.....	44"
Max. wheel weight.....	150lbs
Electric requirement.....	115V 50/60hz 1ph .....or 230V 50/60hz 1ph
Motor.....	1.0 Hp
Cycle time.....	From 6 seconds
Read-outs.....	Gram or Ounce
Accuracy.....	1g or 0.05 oz
Balancing Modes.....	10

### Standard Accessories

Automotive Cone Kit.....1 5/8"-4 1/2"  
"Ziplock" quick nut, pressure cup with rubber scratch proof cap, rim width gauge, calibration tool, storage pegs.



**HOFMANN** 

Hofmann USA  
P.O. Box 178157 Nashville, Tennessee 37217  
(800) 251-4500 (615) 331-7851  
Fax: (615) 331-8176

www.hofmann-usa.com  
info@hofmann-usa.com

*We Reserve the right to make engineering changes without notice.  
Copyright 2002 Hofmann*